

FLI

STAINLESS STEEL PLATFORM "FLOOR" FLI SERIES

Double range STAINLESS steel <u>platform</u>, with approved STAINLESS load cells, suitable for weighing application in industry and any commercial environment. IP68 protection.



The best solution for advanced industrial applications

STAINLESS PLATFORMS: TECHNICAL FEATURES

- Functioning with 4 STAINLESS steel shear-beam load cells (1000 ohm), OIML R60 C3 approved (3000 divisions), IP68 protection degree.
- Monobloc structure in STAINLESS steel, adjustable resting feet and level.
- Fixed STAINLESS steel load surface.
- Max. Power supply 15 Vdc.
- Hermetic junction box, with IP67 protection or IP68 (if integrated with the GELBOX option).
- 3m shielded cable for the connection with the indicator.
- IP68 Watertight connector.

STAINLESS PLATFORMS: OPTIONS

- Connection to the indicator and configuration/calibration at our office.
- Connection to the indicator and calibration with single scale 3000e or double scale 3.000 + 3.000e CE-M approval.
- Support column for the indicator.

DETAIL 1

DETAIL 2





VERSIONS

Available versions						
	l x w x h		Max	d	M	м
Codice	(mm)	N° celle	(kg)	(g)	(g)*	2R (g)*
FLBI1500	1250x1250x120	4x1000kg	600/1500	200/500	500	200/500
FLE13000	1500x1500x120	4x2000kg	1500/3000	500/1000	1000	500/1000



PHOENIX SCALES LTD 34 OLDBURY ROAD WEST MIDLANDS - B70 9ED - WEST BROMWICH - UNITED KINGDOM Tel. 0044 121 520 9048 Fax. 0044 121 557 4006 E-mail sales@phoenixscales.co.uk Web www.phoenixscales.co.uk